

TurfSoft TS2/TS3

For the cleaning of small synthetic grass surfaces with sand and sand/rubber filling

The competent conducted cleaning and maintenance is not only extremely important for the preservation of the playing characteristics and the guaranty of a long durability of the artificial turf pitches. Also the risk of players to be injured can be minimized by constant good athletic conditions of the surfaces.

The TurfSoft TS2 is a solution as simple as effective for the joy in the game and maintaining the value of small areas with infilled surfaces (sand and sand/rubber). Using this machine you can eliminate suspended particles, abrasion and dirt particles from the top surfaces. The manoeuvrable TurfSoft is ideal for areas with little space to move, where stairs, steps and narrow doorways make the access to the artificial turf pitches.

The TurfSoft is equipped with a petrol engine which controls three functions at the same time: the vibrating function of the sieve, the drive of the turbine and the rotation of the cleaning brush. With light pressure on the steering arm the brush steps into the turf and through the emerging feed it causes an easy and energy-saving operation.

The rotating brush absorbs the top layer of the infill material. Afterwards a sieve separates coarse and fine dirt. The suction turbine absorbs the coarse dirt directly into a permanent filter. The cleaned infill material is then spread out dosed by means of a vibrating sieve. The integrated filter can be simply cleaned by turning the hand-wheel.

For operation the front wheels of the TurfSoft are to lock but the fixing can be loosened for transport through narrow doorways. Since the TurfSoft is foldable and equipped with hand grips, it is easy to transport and can be stored space-saving.





TurfSoft TS3

For the cleaning of infilled artificial turf pitches along boards, fences or corner blocks SMG has developed the alternative TurfSoft TS3. Equipped with a hinged side broom the TurfSoft TS3 eliminates the dirt even in areas which are difficult to access. If the side broom is not used, it can be easily folded.



TurfSoft TS2/TS3



1-cylinder petrol engine for brush and turbine



Extractable filter sieve
several sieves available



Hand wheel to clean the permanent filter



Foldable steering arm for easy transport and storing in a small place

**Recommended
accessories for
TurfSoft TS2/TS3**



Easy moving through narrow doorways



FloorTest FT50
Page 83




Gloves
Page 85



Hearing protector
Page 85



Safety glasses
Page 85



Dust mask
Page 85

Chassis	Laser-cut steelframe construction, plastic-coated
Drive	1-cylinder petrol engine / 3,2 kW (4 HP)
Filter box	Permanent filter approx. 5 m ²
Working width	800 mm
Weight	approx. 85 kg
Dimensions	L 980 x W 750 x H 570 mm

Subject to technical alterations