

RotoMatic R58

Grinding machine for elastic synthetic sports surfaces

The grinding machine RotoMatic R58, with its compact construction, is extremely suitable for grinding elastic synthetic sports surfaces, particularly on small areas, boundary zones, alongside curbstones and for projecting boundary lines. The RotoMatic R58 is steered by hand and the operator has a clear view of the work surface and the edge of the grinding disc. Three solid rubber wheels on bearings enable easy manoeuvrability and ensure an accurate and safe operation. The arrangement of the wheels prevents the grinding disc from tilting, even when the surface is uneven.





The grinding disc is mounted on the crankshaft of a 4-stroke petrol engine. In this way the power provided by 13 HP is directly transmitted to the grinding area. The adjustable grinding pressure is set by hand and held constant by the machine. This prevents fast wear of the grinding disc and damage to the surface. For a brief interruption or when the work is finished, the grinding unit can be pivoted upwards by a Bowden cable, and locked in this raised position by a security lever. With a few simple touches the RotoMatic R58 can be folded up for transport or storage and requires little space.

RotoMatic R58



SMG hard metal grinding disc \varnothing 300 mm



Push-rod with control levers for engine speed (accelerator) and for the lifting of the grinding disc



Drive engine and grinding unit in compact construction



Pressure for the grinding disc is manually adjustable

Recommended accessories for RotoMatic R58



Foldable steering arm for easy transport and storing in a small place



TestSet
Page 87




Aluminium shovel
Page 87




Hard metal disc
Page 88



FloorTest FT50
Page 87



Dust mask
Page 89



Hearing protector
Page 89



Safety glasses
Page 89



Gloves
Page 89



Cotton gloves
Page 89



Scraper
Page 89

Chassis	Laser-cut steel frame construction, plastic-coated
Main drive	1-cylinder petrol engine 9.6 kW (13 HP)
Capacity of tank	2.3 liters
Area performance	70 m ² /h
Working width	300 mm
Weight	65 kg
Dimensions	L 800 x W 400 x H 450 mm

Subject to technical alterations